



Subject: How do I clean out and service my MagDrive HHO generator???

It Is a very easy 10 minute process, just follow the simple directions.

- 1, Turn off unit, remove A-Trap fill plug.
- 2, Drain unit using drain plug located on bottom of HHO gen.
- 3, Flush with water and allow to drain.
- 4, Install drain plug and fill the A-trap with vinegar.
- For unit filling instructions use list below
- Single brick use 1 pint vinegar.
- Dual Brick use 1.5 pints of vinegar.
- Triple brick use 2 pints of vinegar.
- Quad Brick use 2.5 pints of vinegar.
- Q-5 Brick used 2.5 pints of vinegar
- 5, Re-install the A-Trap fill plug, top off reserve tank, you are good for another 2 – 3k miles. The reserve tank will top it off automatically. **Remember always and only use Distilled H2o in the resereve tank.**
- 6, Keep in mind when refilling after flush out, the HHO solution will be foamy for the first 20 – 30 minutes. It will clear up and look like bubble water in a short while.
- 7, The vinegar will change color, it will turn a red color once seasoned and as it gets older it will darken.
- 8, Remember you need a good circulation out bound and return flow to the brick from the A-trap. The better the flow the better the results, the higher the A-trap to the brick the better.
- 9, If A-trap/Brick locations cannot be spread apart vertically for circulation. Use an HHO Booster pump on the return line from the A-trap back to the bottom of the Brick cell. Pay attention to the flow direction arrow on the HHO pump, point it towards the Brick.

You are using Distilled White Vinegar a common food item containing distilled water [potable] and a 5% acedic acid solution, meaning no toxic chemicals. The vehicle exhaust according to all certified emissions reports are substantially greener than anything now required by law concerning emissions.

So although all MagDrive units come in color coded models, they all are in essence

"REALLY GREEN ECOLOGICALLY".